

Brache di fune di acciaio

Wire rope slings

BRACHE DI FUNE DI ACCIAIO ZINCATO





con asole impalmate

GALVANIZED WIRE ROPE SLINGS

with hand spliced eyes

DATI TECNICI

TECHNICAL DATA

Codice Code	Codice Code	Fune Rope	Portata ASIT ASIT WLL		Portata ASIM ASIM WLL		Dimensione asole Eyes dimension
			 Kg	 Kg	 Kg	 Kg	
ASIT	ASIM	Ø mm					AxB mm
TTIMP06	TCIMP06	6	372	745	451	901	48 x 96
TTIMP08	TCIMP08	8	649	1.299	736	1.472	64 x 128
TTIMP10	TCIMP10	10	1.025	2.050	1.144	2.288	80 x 160
TTIMP12	TCIMP12	12	1.464	2.929	1.748	3.495	96 x 192
TTIMP14	TCIMP14	14	2.005	4.010	2.382	4.763	112 x 224
TTIMP16	TCIMP16	16	2.631	5.261	3.111	6.222	128 x 256
TTIMP18	TCIMP18	18	3.348	6.696	3.934	7.868	144 x 288
TTIMP20	TCIMP20	20	4.133	8.266	4.862	9.724	160 x 320
TTIMP22	TCIMP22	22	5.008	10.016	5.884	11.767	176 x 352
TTIMP24	TCIMP24	24	5.961	11.922	7.002	14.005	192 x 384
TTIMP26	TCIMP26	26	6.989	13.978	8.214	16.429	208 x 416
TTIMP28	TCIMP28	28	8.131	16.262	9.515	19.030	224 x 448
TTIMP30	TCIMP30	30	9.332	18.664	10.919	21.838	240 x 480
TTIMP32	TCIMP32	32	10.614	21.228	12.425	24.851	256 x 512
TTIMP34	TCIMP34	34	11.983	23.966	14.020	28.040	272 x 544
TTIMP36	TCIMP36	36	13.461	26.923	15.701	31.402	288 x 576
TTIMP38	TCIMP38	38	14.998	29.997	17.503	35.006	304 x 608
TTIMP40	TCIMP40	40	16.619	33.237	19.392	38.784	320 x 640

- Tolleranze in accordo alle norme EN vigenti.
- Tolerances according to EN standards.

Tipo ASIT - Anima tessile - Capi interni

Fune zincata tipo AZN 619 T - AZN 636 T

Lunghezza minima L circa 80 volte il diametro della fune.

ASIT Type - Fiber core

Galvanized wire rope type AZN 619 T - AZN 636 T

The minimum length L is about 80 times the diameter of the rope.

Tipo ASIM - Anima metallica - Capi interni

Fune zincata tipo AZN 719 - AZN 636 AC

Lunghezza minima L circa 80 volte il diametro della fune.

ASIM Type - Steel core - Tail ends protruding from splice

Galvanized wire rope type AZN 719 - AZN 636 AC

The minimum length L is about 80 times the diameter of the rope.

